


Solar Energy South Africa

Suriname Ilt power smart bms



Overview

What is LLT smart BMS?

LLT SMART BMS These smart BMS will fulfill all your Battery management needs, and with the included bluetooth module, you can now check the health of your battery and each individual cell on your phone! No need to open up your board to troubleshoot. Current : constant current of this version BMS can be up to 20A Dimen.

What is the difference between BMS and smart BMS?

BMS with Bluetooth function which will enable user to monitor SOH status of your Battery BMS can support max 300A discharge current with compact design for 12V Back up power application . Smart BMS with elegant design which support UART ,RS485,CAN ,RS232 Communication .

Does smart BMS have a Bluetooth communication module?

Notes:all of our Smart BMS with Bluetooth function will equip a Bluetooth Communication module only , and buyer can choose the PC communication Module separately if needs . please know it kindly in advance ,all orders will be dispatched within 4~5 days without problems .

How to connect a BMS to a battery pack?

A. Firstly ,Please connect bold wires from B- port of the BMS to the negative port of the battery pack . (B- wire should be as short as possible) ,then connect these voltage detection wires (Please take off these wires from the BMS before connecting these wires to the battery to avoid any connection mistakes) B.

Suriname llt power smart bms



36V 48V 60V Li ion or Lifepo4 smart Bluetooth

10S 11S 12S 13S 14S 15S 16S 17S series cell protection for Lithium Battery pack (15*4.2=63V 12*3.65=43.8V Lifepo4 battery pack example),client can select suitable type based on your battery characteristics Dimension (L*W*T)=102*65*12mm Various protection functions for charging and discharging (over-charge, over-discharge,high or Low temperature protection ...

4S~300S master slave multiple series BMS

Introductions and Descriptions : This System can support 48 to Max 500Series Battery Management . This Master to Slave BMS management system which be used to monitor the cell voltage, battery pack total voltage, cell temperature, charge and discharge current and other parameters of the lithium battery system in real time and with high precision, and perform rapid ...

Energy storage(KWh)

102.4kWh

Nominal voltage(Vdc)

512V

Outdoor All-in-one ESS cabinet



LLT smart BMS 4S->22S 40A - ElectricBoardSolutions

Smart BMS with bluetooth app for android and IOS For batteries with a cell count between 4s and 22s arge and discharge current; 40ABalance current; max 160mA Dimension: : 130*60*10mm Includes:* Smart BMS* Built-in Bluetooth* Balance cables* 2x temperature sensor IOS: XiaoxiangBMSAndroid: download hereSPECS:Overcharge LLT smart BMS 4S->22S

200A BMS with low-temp cut-off? , DIY Solar Power Forum

So I think I need a BMS that can handle 200A, and I need it to have a low-temp cut-off so that I don't kill the cells. I've read that the low-temp cutoff doesn't work as advertised for lots of of the available BMS's. I've read great things here about the Overkill BMS, but the 24V version only goes to 100A.



16S 17S 18S 19S 20S Smart BMS with bluetooth

IOS APP display content for our Smart BMS. PC communication and parameters display pages : Product Photo display: 16S,17S,18S,19S 20A BMS with 50A constant discharge current. this BMS can be widely applied on 16S or 17S ...

[14S Li ion Battery BMS Archives](#)

6S to 21S Li ion or Lifepo4 Smart BMS for electric vehicle electric motorcycle with 200A constant current \$ 65.40 - \$ 97.20 Buy it now This product has multiple variants. The options may be chosen on the product page; 8S to 24S Li ion Lifepo4 Smart Bluetooth BMS for 60V 72V 84V battery with UART RS485 CAN communication 100A 150A 200A Constant




200A Smart BMS from LLT Power , Page 4 , DIY Solar Power ...

2 weeks ago purchased a jbd 8s 100a bms from them and payed extra for dhl post as needed it soon. Just got the bms and they sent a 4s



LLT smart BMS 4S->22S 40A - ElectricBoardSolutions

Smart BMS with bluetooth app for android and IOS. For batteries with a cell count between 4s and 22s. Charge and discharge current; 40A Balance current; max 160mA. Dimension: : 130*60*10mm. Includes: * Smart BMS * Built-in ...



Victron compatible LiFePO4 BMS , DIY Solar Power Forum

I have created a VenusOS driver that can talk to BMS/Batteries that has serial communications (instead of the normal CANbus). RS485/RS232/TTL/UART and Venus 2.80+ have been tested. Currently it works with JBD BMS (LLT Power / Overkill Solar) Daly BMS (Daly Smart BMS / Daly Sinowearth based

200A Smart BMS from LLT Power , Page 3 , DIY Solar Power ...

Good Glad you've got it working. Is yours the new shorter black anodized model ? The next revision after the black enclosure models sell out will have a different relay, still JBD with Bluetooth but no enclosure.





6S to 21S Li ion or Lifepo4 Smart BMS for

24V 36V 48V 60V Li ion NCM or Lifepo4 Smart Bluetooth BMS with 80A 100A 120A Constant current for power inverter or Solar energy storage LFP battery Pack with UART CAN RS485 \$ 38.90 - \$ 48.80 Buy it now This product has multiple variants. The options may be chosen on the product page; 13S Active Balance BMS with 60A constant current for 48V

Heltec BMS' (up to 350A) with Active Balancing

Smart BMS of Power Battery - LLT POWER ELECTRONIC Reactions: Dzl. ArthurEld Solar Wizard. Joined Aug 3, 2020 Messages 2,478 Location Hidden Meadow. With the JBD BMS, I suspect its LLT power / JBD Jaibada, but can't confirm. I am however highly confident that I can now spot and verify the JBD BMS by appearance and serial number.



Smart BMS 10S with bluetooth - ElectricBoardSolutions

Smart BMS with bluetooth app for android and IOS Charge and discharge current; 20ABalance current; 50-60mA Dimension: :Max 108*65*10mm Includes:* Smart BMS* Bluetooth module* Balance cables IOS: XiaoxiangBMSAndroid: download hereSPECS:Overcharge detection protection voltage: 4.25+-0.03VOvercharge protection delay time:

[30S to 450S Battery BMS Archives](#)

Smart BMS of Power Battery; 3S to 4S Li ion or Lifepo4 Battery BMS; 5S ~6S Lithium Ion or Lifepo4 Battery PCB board; 7S to 8S li ion or Lifepo4 Battery BMS; 48S 45S 40S 35S 32S lifepo4 Battery high voltage BMS support CAN RS485 Communication for energy storage solar power,UPS,Electric grid Back up Power system



6S 7S 8S 9S 10S 12S 13S 14S 15S 16S 17S 18S 20S smart Bluetooth BMS ...

Features and Characteristics : Characteristics :
This is a smart BMS with UART or RS485,CAN Communication which will be used to protect and monitor your battery status visible from the computer and your android APP phone .which can support parameters setting and adjustment .the charge and discharge port is same .
Constant current : 150A or 200A Application ranges ...


[15S Lifepo4 or Lithium Ion battery BMS](#)

6S 7S 8S 9S 10S 12S 13S 14S 15S 16S 17S 18S 20S smart Bluetooth BMS with 150A to 200A constant current for electric tricycle battery pack \$ 10.80 - \$ 93.90 Buy it now This product has multiple variants. The options may be chosen on ...



[10S Lithium Ion Battery BMS Archives](#)


6S to 17S li ion or Lifepo4 smart BMS with CAN RS485 UART communication 60A 80A 100A 120A



constant current for 36V 48V 60V BMS \$ 38.90 - \$ 48.80 Buy it now This product has multiple variants. The options may be chosen on the product page; 4S to 22S lithium or Lifepo4 battery Smart Bluetooth BMS with 100A constant current with internal Bluetooth

Victron VenusOS driver for serial connected BMS

I have created a VenusOS driver that can talk to BMS/Batteries that has serial communications (instead of the normal CANbus). RS485/RS232/TTL/UART and Venus 2.80+ have been tested. Currently it works with JBD BMS (LLT Power / Overkill Solar) Daly BMS (Daly Smart BMS / Daly Sinowearth based



4S 200A BMS Lifepo4 Battery 3S 12V Li-Ion

Features and Characteristics : Characteristics : this is a smart BMS with Bluetooth and PC communication which will be used to protect and monitor your battery status visible from the computer and your android APP phone .which can support UART or UART and RS485 communication .the charge and discharge port is same . Size :232*105*20mm, constant ...

200A Smart BMS from LLT Power , Page 2 , DIY Solar ...

@AussieSim I assume that is an LLT BMS, could you provide a link to it. If you got any docs, that would be helpful too. Is that "Box" pre-attached to the PCB or is that your handy work ? I like that

solid copper ...



7-14s JBD / LLT Bluetooth Smart BMS (JBD-SP14S004)

The JBD/LLT 14s smart BMS is an awesome addition to any battery build. This smart-detecting BMS can automatically range (when wired according to the instructions) between 7 and 14s. This allows for use in a wide variety of builds and use-cases. In addition, this is one of the smallest 14s bluetooth BMS's on the market. Measuring in at just 63 x 52 x 12mm, it offers a ton of features ...

GitHub

BMSs from lithiumbatterypcb aka LLT Power 'Xiaoxiang' BMS; Some BMS's Labelled "Smart BMS" Aka, if your board looks like this: It is probably going to work. Mine was a 21s so it had two of the 16 pin JST connectors at the base. All cell counts should work. You can always check if the UART protocol matches the protocol linked at the bottom



Good BMS for 10s10p battery : r/ElectricSkateboarding

As for a good BMS an LLT smart BMS with Bluetooth is a very good option for large capacity packs. ESP32 is a series of low cost, low power



system on a chip microcontrollers with integrated Wi-Fi and dual-mode Bluetooth. The ESP32 series employs either a Tensilica Xtensa LX6, Xtensa LX7 or a RiscV processor, and both dual-core and single

Contact Us

For catalog requests, pricing, or partnerships, please visit:
<https://ian-solar.co.za>